Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

Inspect	ion Date: 02/10/2020	or and any c	iocumentation prov	vided with the msurane	poney
	Information				
Owner		uster Homes Improvement A	ssociation unit Four INC	Contact Person:	
	s: 115 125 135 145 155 F		ssociation unit rour inc	Home Phone:	
	Oldsmar	Zip: 34677		Work Phone:	
County		1 04077		Cell Phone:	
	ace Company:			Policy #:	
Year o	f Home: 1979	# of Stories:		Email:	
	1979				
accom	: Any documentation used in v pany this form. At least one pl 17. The insurer may ask addit	otograph must accompa	any this form to valid	late each attribute marke	d in questions 3
	ilding Code: Was the structure b HVHZ (Miami-Dade or Broward	d counties), South Florida	Building Code (SFBC	C-94)?	
	A. Built in compliance with the a date after 3/1/2002: Building	Permit Application Date (MM/DD/YYYY)//		
	B. For the HVHZ Only: Built in provide a permit application wi	th a date after 9/1/1994: E	Building Permit Applic		
X	C. Unknown or does not meet the	he requirements of Answe	er "A" or "B"		
OR	of Covering: Select all roof covering: Year of Original Installation/Repering identified.				
cov		Permit Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance
	■ 1. Asphalt/Fiberglass Shingle	9/-5-/19	FL#10124	2019	
	2. Concrete/Clay Tile				
					_
	6. Other	/			
X	A. All roof coverings listed abounstallation OR have a roofing p				
	B. All roof coverings have a Miroofing permit application after				
	C. One or more roof coverings	do not meet the requireme	ents of Answer "A" or	"B".	
	D. No roof coverings meet the r	requirements of Answer "	A" or "B".		
3. Ro	of Deck Attachment: What is th	e weakest form of roof de	eck attachment?		
	A. Plywood/Oriented strand box by staples or 6d nails spaced at shinglesOR- Any system of s mean uplift less than that requir	6" along the edge and 1 crews, nails, adhesives, of	2" in the fieldOR- Ither deck fastening sys	Batten decking supporting	wood shakes or wood
	B. Plywood/OSB roof sheathin 24"inches o.c.) by 8d common other deck fastening system or a maximum of 12 inches in the	nails spaced a maximum truss/rafter spacing that is	of 12" inches in the fie shown to have an equ	eldOR- Any system of sci iivalent or greater resistanc	rews, nails, adhesives,
	C. Plywood/OSB roof sheathin 24"inches o.c.) by 8d common decking with a minimum of 2 n Any system of screws, nails, ac	nails spaced a maximum lails per board (or 1 nail p lhesives, other deck faste	of 6" inches in the fie per board if each board ning system or truss/ra	ldOR- Dimensional lum I is equal to or less than 6 in after spacing that is shown	ber/Tongue & Groove inches in width)OR-to have an equivalent
Inspec	tors Initials///Property Ac	Idress 115 125 13	5 145 155 P00le	Pl, Oldsmar, FL 34	0//

		or greater resistance to 182 psf.	han 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least
	П	D. Reinforced Concre	rete Roof Deck.
	П	F. Unknown or unide	
		G. No attic access.	All I de la constant
4			4. What is the WEAVECT as Care all sometries 9 (Decoration) at the decorate of Chin/ all a in head in
	5 fe	eet of the inside or outs	t: What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks within side corner of the roof in determination of WEAKEST type)
	X	A. Toe Nails	
			rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to plate of the wall, or
		X Metal o	connectors that do not meet the minimal conditions or requirements of B, C, or D
	Miı	nimal conditions to qu	ualify for categories B, C, or D. All visible metal connectors are:
			d to truss/rafter with a minimum of three (3) nails, and
			ed to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from cking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe on.
		B. Clips	
		☐ Metal o	connectors that do not wrap over the top of the truss/rafter, or
			connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail n requirements of C or D, but is secured with a minimum of 3 nails.
		C. Single Wraps	
		minimu	connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a um of 2 nails on the front side and a minimum of 1 nail on the opposing side.
		D. Double Wraps	
		beam, o	Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with mum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or
			connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on des, and is secured to the top plate with a minimum of three nails on each side.
		E. Structural Ar	nchor bolts structurally connected or reinforced concrete roof.
		F. Other:	
		G. Unknown or unide	entified
		H. No attic access	
5.			the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of enclosed space in the determination of roof perimeter or roof area for roof geometry classification).
		A. Hip Roof Hi	p roof with no other roof shapes greater than 10% of the total roof system perimeter.
		To	otal length of non-hip features: feet; Total roof system perimeter: feet of on a building with 5 or more units where at least 90% of the main roof area has a roof slope of
			ss than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft
	X	C. Other Roof Ar	ny roof that does not qualify as either (A) or (B) above.
6.		A. SWR (also called sheathing or foam	ance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the ter intrusion in the event of roof covering loss.
		C. Unknown or unde	termined.
Ins		etors Initials MPr	
± nr	1. •		alid for up to five (5) years provided no metarial changes have been made to the structure or

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7. <u>Opening Protection</u>: What is the <u>weakest</u> form of wind borne debris protection installed on the structure? **First**, use the table to determine the weakest form of protection for each category of opening. **Second**, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings **and** (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

	ening Protection Level Chart an "X" in each row to identify all forms of protection in use for each	Glazed Openings		Non-Glazed Openings			
openi form	ng type. Check only one answer below (A thru X), based on the weakest of protection (lowest row) for any of the Glazed openings and indicate eakest form of protection (lowest row) for Non-Glazed openings.	Windows or Entry Doors	Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors
N/A	Not Applicable- there are no openings of this type on the structure		Х	Х	Χ		Χ
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)						
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)						
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007						
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance						
N	Opening Protection products that appear to be A or B but are not verified						
IN	Other protective coverings that cannot be identified as A, B, or C						
Х	No Windborne Debris Protection	Х				Х	

- A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above).
 - Miami-Dade County PA 201, 202, and 203
 - Florida Building Code Testing Application Standard (TAS) 201, 202, and 203

☐ A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist

- American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996
- Southern Standards Technical Document (SSTD) 12
- For Skylights Only: ASTM E 1886 and ASTM E 1996
- For Garage Doors Only: ANSI/DASMA 115

A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above
A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above
3. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed
penings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection device
n the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following
or "Cyclic Pressure and Large Missile Impact" (Level B in the table above):
• ASTM E 1886 <u>and</u> ASTM E 1996 (Large Missile – 4.5 lb.)
• SSTD 12 (Large Missile – 4 lb. to 8 lb.)
• For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile - 2 to 4.5 lb.)

□ B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist
 □ B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X

B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above

☐ B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above

□ <u>C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007</u> All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above).

C.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist

☐ C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above

☐ C.3 One or More Non-Glazed openings is classified as Level N or X in the table above

Inspectors Initials Property Address 115 125 135 145 155 Poole Pl, Oldsmar, FL 34677

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

N. Exterior Opening Protection (unverified shutter sprotective coverings not meeting the requirements of Ar	nswer "A", "B", or C" or systems th	
with no documentation of compliance (Level N in the ta	·	
 N.1 All Non-Glazed openings classified as Level A, B, C, o N.2 One or More Non-Glazed openings classified as Level I 		• •
table above		
□ N.3 One or More Non-Glazed openings is classified as Leve		
X. None or Some Glazed Openings One or more Glaze	ed openings classified and Level X	in the table above.
MITIGATION INSPECTIONS MUST B Section 627.711(2), Florida Statutes, provi	ides a listing of individuals who me	ay sign this form.
Qualified Inspector Name: Robert Martin	Home inspector	License or Certificate #: HI7816
Inspection Company: RMC Inspections, LLC	Phone:	727-422-7688
Qualified Inspector – I hold an active license as a	: (check one)	
Mome inspector licensed under Section 468.8314, Florida Statute training approved by the Construction Industry Licensing Board	es who has completed the statutory num	ber of hours of hurricane mitigation
\square Building code inspector certified under Section 468.607, Florida	Statutes.	
General, building or residential contractor licensed under Section	·	
Professional engineer licensed under Section 471.015, Florida St		
 □ Professional architect licensed under Section 481.213, Florida St □ Any other individual or entity recognized by the insurer as posse 		oporty complete a uniform mitigation
verification form pursuant to Section 627.711(2), Florida Statute		operty complete a uniform mitigation
Individuals other than licensed contractors licensed under under Section 471.015, Florida Statues, must inspect the structure Licensees under s.471.015 or s.489.111 may authorize a director of conduct a mitigation verification inspection.	Section 489.111, Florida Statutes, ructures personally and not through the end of the property of the instance of inspection	gh employees or other persons. Equisite skill, knowledge, and spection or (licensed erform the inspection ector) ulent mitigation verification form is ministrative action by the tutes) The Qualified Inspector who d mitigation inspector personally lid perform an inspection of the rized Representative.
		
An individual or entity who knowingly provides or utters a obtain or receive a discount on an insurance premium to w of the first degree. (Section 627.711(7), Florida Statutes)		
The definitions on this form are for inspection purposes on as offering protection from hurricanes.	•	
Inspectors Initials Property Address 115 125 1	35 145 155 Poole Pl, Olds	smar, FL 34677
*This verification form is valid for up to five (5) years prov		
inaccuracies found on the form.	no marchael changes have be	
OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155		Page 4 of 4



STATE OF FLORIDA DEPARTMENT OF BUSINESS AND PROFESSIONAL REGULATION

HOME INSPECTORS LICENSING PROGRAM

THE HOME INSPECTOR HEREIN IS CERTIFIED UNDER THE PROVISIONS OF CHAPTER 468, FLORIDA STATUTES

MARTIN, ROBERT W

728 5TH AVE NE LARGO FL 33770

LICENSE NUMBER: HI7816

EXPIRATION DATE: JULY 31, 2020

Always verify licenses online at MyFloridaLicense.com



Do not alter this document in any form.

This is your license. It is unlawful for anyone other than the licensee to use this document.





RMC Incpections, LLC rmcinspections@gmail.com

Exterior Photos



Side



Side



Rear



Wind Mitigation Photos



RMC Incpections, LLC rmcinspections@gmail.com

Roof Deck Attachment

MT6



Nail Spacing



Nail Type



Wind Mitigation Photos



RMC Incpections, LLC rmcinspections@gmail.com

Roof To Wall Connection

Back Side



Other



New Photo	SWR/Permit
	VR